

PYTHON

LWIR Thermal Camera

Python is a versatile and ultra-compact LWIR camera core offering a comprehensive suite of features including Camera Link, GigE, USB 3.0 or CMOS digital outputs.



.....
get ENHANCED VISION

VERSATILE, RUGGED AND RELIABLE

Python's exceptional sensitivity coupled with advanced digital image enhancement allows for a new reference point when it comes to sharpness and clarity of infrared images. Additionally, it's standard 60 Hz frame rate provides best image quality for fast moving objects in a low power and compact package.



FEATURES

- 30 and 60 Hz frame rate
- No availability restrictions
- 14-bit and 8-bit digital data
- NTSC/PAL analog video
- Intuitive user interface
- Low power consumption
- Built-in image processing capabilities

APPLICATIONS

- Homeland Security & Border protection
- Thermal weapon sight
- Hand-held and helmet mounted thermal viewers
- Security, Surveillance, Reconnaissance
- Light payloads for UAVs, marine & land vehicles
- Firefighting & Pyrometric
- Medical & Industrial Imaging

VERSATILITY

- Camera Link
- GigE
- USB 3.0
- Available resolution
 - 640 x 480
 - 384 x 288
- Various lens options
- Lens-less option
- Various custom options

SPECIFICATIONS

	Python
Array Type	640 x 480 a-Si Microbolometer 384 x 288 a-Si Microbolometer
Pixel Pitch	17 micron
Spectral Band	8.0 to 14.0 micron
NETD/ Performance	< 50 mK @ f/1.0
Analog Output	30/25 Hz (NTSC/PAL)
Digital Output	Camera Link
14 or 8-bit	GigE/USB 3.0/3.3V parallel CMOS/Serial LVDS
Digital Frame Rate	60/50 Hz (NTSC/PAL) max
Input Voltage	4 to 5.5 VDC 6 to 12 VDC for Camera Link, GigE, USB 3.0 Options
Power Requirements	< 1.2 W < 1.6 W for Camera Link Option < 2.7 W for GigE or USB 3.0 Option
Time to Image	<4 seconds
Size without lens	1.6" x 1.6" x 1.1" 1.6" x 1.6" x 1.6" for Camera Link Option 1.6" x 1.6" x 1.8" for GigE Option or USB 3.0 Option
Weight without lens	50 g 150 g for Camera Link Option 170 g for GigE Option or USB 3.0 Option
Operating Temperature Range	-40°C to + 60°C
Non-Operating Temperature Range	-45°C to + 85°C
Scene Temperature Range	-40°C to + 150°C; -40°C to + 500°C
Environmental Specifications	Meets common application's Shock, Vibration, Humidity, Operation Altitude requirements
ROHS	Compliant
REACH, WEEE, Mil-Spec	Provided on request
Image Processing	2x,4x, 8x Digital zoom;Image Orientation; Digital Filtering (de-noising, sharpening, contrast enhancement); Built-in Self-Test; Image Optimization (BPR, NUC, AGC/LAP)
Camera Control	SDK or GUI
Digital Interface	Camera Link, GigE, USB 3.0, LVCMOS level, LVDS, UART, RS-232, external sync input/output

STANDARD LENS OPTIONS

- Fixed focus: 7.5, 13, 17, 25, 35, 50 mm
- Zoom: 35 – 105 mm
- Lens-less option

ACCESSORIES

- SDK
- Video Processing Module Kit
- Focus Tool
- Tripod Mount Adapter
- Locking Nut and O-ring
- Locking Nut Tool
- Wearsaver
- Advanced Image Processing Software

4 A (1), GMR Hyderabad Aviation SEZ,
RGIA Airport, Shamshabad
Hyderabad - 500108
Telangana, India.

e: sales@anlineartech.com
t: +91-40-65555708
m: +91-98483 72063, +91-99599 55506
w: www.anlineartech.com

ANALINEAR
TECHNOLOGIES
.....
get ENHANCED VISION